

Scrutineering Checklist

All Events

EP-101f



PLEASE CHECK THE FOLLOWING LIST TO ENSURE YOUR VEHICLE IS COMPLIANT AND MAKE RECTIFICATIONS PRIOR TO AN EVENT.
THIS WILL ASSIST IN SCRUTINEERING BY STAFF ON THE DAY.

INSPECTION DATE

 – –

Office Use:

EXTERNAL

DRIVER
Pass

SCRUTINEER
Pass

1	Tires–type for rear, tread wear 300 or higher (eg: 400, 500, etc)		
2	Stoptlights / Taillights / Headlights Taped (clear film preferred if glass)		
3	Wiper / Washers		
4	Wheels secured firmly (check all nuts are present)		
5	Windscreen–check for clear visibility and no cracks		
6	All types of fluid leaks		
7	All body panels present and fitted securely		
8	Sideways fitted exhaust protrude between 50–150mm from bodywork Rearward fitted exhaust must finish past rear axles and finish away from bodywork		

BOOT

Pass

Pass

1	Battery–safely secured / Battery Triangle Affixed		
2	No loose objects		
3	Fuel sources isolated from driver cabin and no leaks		

ENGINE BAY

Pass

Pass

1	Check for fluid leaks		
2	Check – brake fluid level		
3	Battery–safely secured / Battery Triangle Affixed		
4	Accelerator – Must be free of binding, throttle return springs safely attached		
5	Check for holes in firewall		
6	Secondary bonnet restraint (for main circuit)		
7	Crank case breather/ Catch can if fitted minimum 2 litres for <2000cc engine or 3 litres for >2000cc engine		

INTERIOR OF CAR

Pass

Pass

1	Steering wheel –secure, grip not loose		
2	Seat belts harnesses –secured, sound operation and condition		
3	Front seats –secured firmly		
4	Brake pedal –NOT low or spongy		
5	Fire extinguisher – 1kg minimum, secured by metal bracket fixed securely, in reach of driver and less than 3 years old (recommended)		
6	Doors – mechanisms functioning and able to be opened from inside and outside		
7	No loose objects		
8	My Laps module installed (Main Circuit Only)		
9	Helmet –complies with FIA 8860–2010, FIA8860–2004, AS1698, SFI24.1, ECE22.05 and Snell SA2000 no physical damage and must have approval sticker affixed		

UNDER CAR

Pass

Pass

1	Suspension –check for correct operation		
2	Exhaust –check for secure mounting and noise limit (95 db at 30m from track edge)		